

## UB-5338C Panaboard

Colour scanning system with 2 surfaces

SD Memory card / USB flash memory storage

Colour output with recommended colour printer

Delivered with markers (black, red, blue) and one eraser

Panel dimensions: 84 x 138 cm (HxW)

Delivered with wall-mounted kit



Colour Electronic Copy Board

### Input

<b>Copying Area (HxW)</b>	790 x 1.360
---------------------------	-------------

### Panel Dimension (mm)

<b>Height</b>	838.0
---------------	-------

<b>Width</b>	1378.0
--------------	--------

<b>Panel Surface</b>	2 (endless scroll type)
----------------------	-------------------------

<b>Scanning System</b>	Contact Image Sensors
------------------------	-----------------------

<b>Scanning Size</b>	Standard-size
----------------------	---------------

### System Requirements

<b>Computer</b>	IBM PC/ AT or compatible machine with a CD-ROM drive
-----------------	--

<b>CPU</b>	Pentium® II or higher processor
------------	---------------------------------

<b>Interface</b>	USB 2.0 (Full Speed, USB Slave, B-Type Connector)
------------------	---

<b>OS</b>	Windows Vista®, Windows®XP (SP2 or higher) Windowsm 2000 (SP4 or higher)
-----------	--

<b>Memory</b>	Windows XP: 256 MB or more, Windows 2000: 128 MB or more
---------------	--

<b>HDD</b>	At least 100 MB free space
------------	----------------------------

### General

<b>Display</b>	1.8" Colour LCD
----------------	-----------------

#### Dimensions (mm)

<b>Width</b>	1636.0
<b>Depth</b>	224.0
<b>Height</b>	1125.0
<b>Weight (kg)</b>	26.0

#### Power Supply

<b>Herz (Hz)</b>	50 - 60 Hz
<b>Voltage (V)</b>	220 - 240 V

#### Power Consumption

<b>Operational</b>	0,35 A
<b>Standby mode</b>	0,15 A

#### Operating Environment

<b>Temperature</b>	10-35 degrees C
<b>Humidity</b>	30-80% RH
<b>Standard Accessories</b>	Clock Battery (CR2032) ,USB cable (2.4 m 17 ft.) Markers (1 black, 1 red and 1 blue), 1 Eraser