

UB-7325 Panaboard

Built-in printer for easy-operation (plain paper)

4 panels

USB PC Interface

15 seconds per sheet copy speed

Can be wall-mounted or used with floor-stand option

Delivered with markers (black, red and blue) and one thermal transfer film



Electronic Copy Board

Input

Panel Dimension (mm)

Height	1400.0
Width	900.0
Panel Surface	4 (endless type)
Scanning System	Contact Image Sensors

System Requirements

Computer	IBM® PC/AT or compatible machine with a CD-ROM drive
CPU	Pentium® II or higher processor
Interface	USB 1.1
OS	Windows® 98, Windows® Me, Windows® 2000, Windows® XP
HDD	At least 40 MB free space

General

Dimensions (mm)

Width	1648.0
Depth	264.0
Height	1396.0
Weight (kg)	42.0

Power Supply

Herz (Hz)	50/60 Hz
Voltage (V)	AC 100-120V or AC 220-240V

Power Consumption

Operational	1.40 A (AC 100-120V) 0.75 A (AC 220-240V)
Standby mode	0.2 A (AC 100 - 120 V)

Operating Environment

Temperature	10-35 degrees C
Humidity	30-80% RH
Standard Accessories	Markers (One black, red and blue) Eraser Printer Driver Document Manager and Document Viewer Software Thermal Transfer Film and 20 A4 Size Test Sheets
